

## SECTION II

CORRECTIONS TO C. G. LIGHT LIST, VOLUME I LIGHT LIST, 2000							
(1) No.	(2) Name and Location	(3) Position	(4) Characteristic	(5) Height	(6) Range	(7) Structure	(8) Remarks
3290	Green Island Seal Ledges Whistle Buoy SL East of ledges.						<i>Remove from list.</i>
							* 48/00
3300	<i>Penobscot Bay East Approach Lighted Whistle Buoy WP</i>	43 55 37 N 68 39 37 W	<b>Mo (A) W</b>		6	Red and white stripes with red spherical topmark.	
	*	*					48/00
*3302	Penobscot Bay Buoy 2					Red nun.	
							48/00
4045	Perry Ledge Buoy 2A						<i>Remove from list.</i>
							* 48/00
4055	Twenty-five Foot Rock Buoy 9 East of shoal.	44 01 40 N 69 01 18 W				Green can.	
	*	*					48/00
<b>PENOBSCOT BAY AND APPROACHES (Chart 13302)</b>							
<b>Two Bush Channel</b>							
4520	Rockweed Shoal Buoy 7 Marks 32-foot shoal.	43 58 32 N 69 01 22 W				Green can.	
	*	*				*	48/00
4545	- Rock Buoy 2 Marks southside of 22-foot rock.						<i>Remove from list.</i>
							* 48/00
4555	<i>Two Bush Ledge Lighted Bell Buoy 5TB</i> Marks south side of 28-foot shoal.	43 56 47 N 69 04 55 W	<b>FI G 4s</b>		4	Green.	
	*	*	*			*	48/00
4570	Devils Half Acre Buoy 4	43 55 36 N 69 08 52 W				Red nun.	
	*	*				*	48/00
<b>LONG ISLAND SOUND (Western Part) (Chart 12363)</b>							
21275	<b>Old Field Point Light</b>	40 58 37 N 73 07 07 W	<b>AI R G 24s</b> R fl 12s ec. G fl 12s ec.	74	14	Black tower on granite house.	
		*			*		48/00
26155	- RANGE FRONT LIGHT	40 56 52 N 73 04 19 W	<b>Q R</b>	32		KRW on pile.	
		*		*			48/00
*26861	- Buoy 7					Green can.	Private aid.
							48/00

**Note:** Asterisks (\*) indicate that column(s) in which a correction has been made or new information added.  
Denotes a new entry when preceeding the station number.

## SECTION II

CORRECTIONS TO C. G. LIGHT LIST, VOLUME I LIGHT LIST, 2000							
(1) No.	(2) Name and Location	(3) Position	(4) Characteristic	(5) Height	(6) Range	(7) Structure	(8) Remarks
*26862	- Buoy 8				Red nun.	Private aid.	48/00
*26863	- Buoy 9				Green can.	Private aid.	48/00
*26864	- Buoy 10				Red nun.	Private aid.	48/00
*28141	Shelter Island Sound Aquaculture Buoy				Yellow nun.		48/00

CORRECTIONS TO C. G. LIGHT LIST, VOLUME II LIGHT LIST, 2000							
(1) No.	(2) Name and Location	(3) Position	(4) Characteristic	(5) Height	(6) Range	(7) Structure	(8) Remarks
920	- North Jetty Danger Buoy A				White and orange; can.		
	*						48/00
950	- Lighted Buoy 9		FI G 2.5s		4 Green.		
					*		48/00
1460	- RANGE REAR LIGHT 660 yards, 327° from front light.		F W	40	14 KRW on white skeleton tower.	Visible on range line only.	
					*		48/00
<b>Delaware Bay (West Side)</b>							
<b>Harbor of Refuge</b>							
2030	DELAWARE BREAKWATER WEST END LIGHT 1		FI G 4s	45	7 SG on tower.		
					*		48/00
<b>CAPE HENLOPEN TO INDIAN RIVER INLET (Chart 12216)</b>							
<b>Roosevelt Inlet</b>							
2065	- JETTY LIGHT 1R	38 47 38 N 75 09 22 W	FI G 4s	21	4 SG on skeleton tower on piles.	Higher intensity beam toward 004°.	
		*			*		48/00
2085	LEWES AND REHOBOTH CANAL JETTY WARNING LIGHT	38 41 15 N 75 05 52 W	FI W 4s	15	6 NW on skeleton tower, on white cylindrical base; worded DANGER SUBMERGED JETTY.		
		*					48/00
<b>Port Mahon</b>							
2345	- DIRECTIONAL LIGHT	39 10 42 N 75 24 24 W	Oc W 4s	14	6 On skeleton tower.	Visible all around; higher intensity to northeast.	
					*		48/00

**Note:** Asterisks (\*) indicate that column(s) in which a correction has been made or new information added.  
Denotes a new entry when preceeding the station number.

## SECTION II

CORRECTIONS TO C. G. LIGHT LIST, VOLUME II LIGHT LIST, 2000							
(1) No.	(2) Name and Location	(3) Position	(4) Characteristic	(5) Height	(6) Range	(7) Structure	(8) Remarks
2410	LITTLE RIVER LIGHT 2	39 09 41 N 75 24 29 W	FI R 4s	23	6	TR on pile.	Higher intensity beam to the southeast.
					*		48/00
*4991.01	- Buoy 1A					Green can.	Private aid.
							48/00
*4991.41	- Buoy 5A					Green can.	Private aid.
							48/00
*4991.51	- Buoy 6A					Red nun.	Private aid.
							48/00
*4991.52	- Buoy 6B					Red nun.	Private aid.
							48/00
*4991.61	- Buoy 7A					Green can.	Private aid.
							48/00
*4991.62	- Buoy 7B					Green can.	Private aid.
							48/00
*4991.71	- Buoy 8A					Red nun.	Private aid.
							48/00
<b>Chincoteague Channel</b>							
5315	- Lighted Buoy 11	37 52 45 N 75 24 03 W	FI G 4s		4	Green.	
		*					48/00
*Delete Headings: *CAPE CHARLES TO WOLF TRAP (Chart 12224) *Virginia Inside Passage							
6265	- Daybeacon 196					TR on pile.	
							48/00
*Add Headings: *CHESAPEAKE BAY ENTRANCE (Chart 12221) *Virginia Inside Passage							
6320	- Daybeacon 206	37 24 30 N 75 50 18 W				TR on pile.	
							48/00
*AddHeadings: *CAPE CHARLES TO WOLF TRAP (Chart 12224) *Virginia Inside Passage							
6355	- Daybeacon 215	37 23 24 N 75 51 12 W				SG on pile.	
							48/00
6635	- Lighted Buoy 7	37 34 42 N 75 36 55 W	FI G 4s		4	Green.	
		*					48/00

**Note:** Asterisks (\*) indicate that column(s) in which a correction has been made or new information added.  
 Denotes a new entry when preceeding the station number.

## SECTION II

CORRECTIONS TO C. G. LIGHT LIST, VOLUME II LIGHT LIST, 2000							
(1) No.	(2) Name and Location	(3) Position	(4) Characteristic	(5) Height	(6) Range	(7) Structure	(8) Remarks
<b>Eastern Branch</b>							
10332	- Buoy 1EB					Green can.	Private aid.
	*					*	48/00
*10332.01	- Buoy 2EB					Red nun.	Private aid.
							48/00
*11521.1	- Daybeacon 15					SG on pile.	Private aid.
							48/00
*11521.2	- Daybeacon 16					TR on pile.	Private aid.
							48/00
*11521.3	- Daybeacon 17					SG on pile.	Private aid.
							48/00
*11521.4	- Daybeacon 18					TR on pile.	Private aid.
							48/00
*11521.5	- Daybeacon 19					SG on pile.	Private aid.
							48/00
12143.7	Barretts Point Lighted Buoy 2		FI R 2.5s		4	Red.	Replaced by nun from Nov. 30 to Apr. 30. Private aid.
							* 48/00
12143.71	Barretts Point Daybeacon 3					SG on pile.	Private aid.
							* 48/00
12143.72	Barretts Point Daybeacon 4					TR on pile.	Private aid.
							* 48/00
12195	- DAM LIGHT A	37 24 22 N 76 56 21 W	FI W 2.5s	10		Daymark on pile worded DANGER KEEP AWAY, DAM SPILLWAY.	Private aid.
	*	*	*				* 48/00
*12195.1	- DAM LIGHT B	37 24 23 N 76 56 18 W	FI W 2.5	10		Daymark on pile worded DANGER KEEP AWAY, DAM SPILLWAY.	Private aid.
							48/00
*37083	Chesapeake Outfall Warning Daybeacon A	36 44 09 N 76 17 42 W		12		NW on bridge pile.	Private aid.
							48/00
*37083.1	Chesapeake Outfall Warning Daybeacon B					NW on bridge pile.	Private aid.
							48/00

**Note:** Asterisks (\*) indicate that column(s) in which a correction has been made or new information added.  
Denotes a new entry when preceeding the station number.

## SECTION II

CORRECTIONS TO C. G. LIGHT LIST, VOLUME II LIGHT LIST, 2000							
(1) No.	(2) Name and Location	(3) Position	(4) Characteristic	(5) Height	(6) Range	(7) Structure	(8) Remarks
<b>ALBEMARLE SOUND TO NEUSE RIVER (Chart 11553)</b>							
<b>Albemarle Sound</b>							
37825	- NORTH LIGHT N	36 06 08 N 75 54 44 W	<b>Iso W</b> 6s	21	6	NB-I on multipile structure.	Light equipment removed when endangered by ice.
		*					48/00
CORRECTIONS TO C. G. LIGHT LIST, VOLUME III LIGHT LIST, 2000							
(1) No.	(2) Name and Location	(3) Position	(4) Characteristic	(5) Height	(6) Range	(7) Structure	(8) Remarks
<b>Ashley River</b>							
3570	- APPROACH RANGE	32 46 24 N	<b>Q R</b>	20		KRW-I on dolphin.	Visible 2° each side of range line.
34590	FRONT LIGHT	79 57 06 W	<b>FI R</b> 4s	21	3		Passing light visible all around.
							* 48/00
6465	- RANGE FRONT LIGHT	30 43 00 N 81 18 00 W	<b>Q W</b> (Day) <b>Q W</b> (Night) <b>(4) Mo (U) W</b>	45 51 47		KRW on tower.	DAY: Visible 1.5° each side of range line NIGHT: Visible 4° each side of range line. Obstruction lights on NE, NW, SE, and SW corners. HORN: Mo U (••-) Sound signal operates continuously.
							* 48/00
6470	- RANGE REAR LIGHT 3,021 yards, 291.3° from front light.		<b>Oc W</b> 4s (Day) <b>Oc W</b> 4s (Night) <b>(2) Mo (U) W</b>	121 127 51		KRW on tower.	DAY: Visible 1.5° each side of range line. NIGHT: Visible 4° each side of range line. Obstruction lights on NW and SE corners. HORN: Mo U (••-) Sound signal operates continuously.
							* 48/00
22600.5	- RANGE FRONT PASSING LIGHT	27 41 50 N 82 32 50 W	<b>FI W</b> 4s	17	5	On same structure as Cut C Channel Range Front Light.	
							* 48/00
22605.5	- RANGE REAR PASSING LIGHT	27 42 12 N 82 32 16 W	<b>FI W</b> 4s	20	5	On same structure as Cut C Channel Range Rear Light.	
	*						* 48/00
22760	- RANGE FRONT LIGHT	27 45 48 N 82 31 14 W	<b>Q W</b>	15		KGB on small house on piles.	Lighted throughout 24 hours.
							* 48/00
22760.5	- RANGE FRONT PASSING LIGHT	27 45 48 N 82 31 14 W	<b>FI W</b> 4s	17	5	On same structure as Cut E Channel Range Front Light.	
							* 48/00

**Note:** Asterisks (\*) indicate that column(s) in which a correction has been made or new information added.  
Denotes a new entry when preceeding the station number.

## SECTION II

CORRECTIONS TO C. G. LIGHT LIST, VOLUME III LIGHT LIST, 2000							
(1) No.	(2) Name and Location	(3) Position	(4) Characteristic	(5) Height	(6) Range	(7) Structure	(8) Remarks
22765	- RANGE REAR LIGHT 1,271 yards, 017.9° from front light.		<b>Iso W</b> 6s	50		KGB on skeleton tower on piles.	Lighted throughout 24 hours.  * 48/00
22765.5	- RANGE REAR PASSING LIGHT	27 46 25 N 82 31 01 W	<b>FI W</b> 4s	20	5	On same structure as Cut E Channel Range Rear Light.	* 48/00
23940	- LOWER RANGE FRONT LIGHT	27 48 30 N 82 34 42 W	<b>FI W</b> 2.5s	17		KRW on skeleton tower on piles.	Visible 1.5° each side of rangeline. Lighted throughout 24 hours.  * 48/00
24485	- Shoal Daybeacon	27 43 48 N 82 29 54 W				NW on pile worded DANGER SHOAL.	  * 48/00
*25765.5	- Daybeacon 2					TR on pile.	48/00
<b>Little River - Winyah Bay</b>							
34100	- LIGHT 96	33 17 54 N 79 17 12 W	<b>FI R</b> 2.5s	16	3	TR-TY on dolphin.	  * 48/00
*34100.5	- Daybeacon 97					SG-SY on pile.	48/00
34590 3570	ASHLEY RIVER APPROACH RANGE FRONT LIGHT	32 46 24 N 79 57 06 W	<b>Q R</b> <b>FI R</b> 4s	20 21	3	KRW-I on dolphin.	Visible 2° each side of range line. Passing light visible all around.  * 48/00
<b>*Add Heading: *Morro Bay Channel</b>							
*55275.1	- Daybeacon 97					SG on pile.	Private aid.  48/00
*55275.2	- Daybeacon 99					SG on pile.	Private aid.  48/00

CORRECTIONS TO C. G. LIGHT LIST, VOLUME IV LIGHT LIST, 2000							
(1) No.	(2) Name and Location	(3) Position	(4) Characteristic	(5) Height	(6) Range	(7) Structure	(8) Remarks
954	<b>Samedan-EC-320 RACON</b>	28 12 48 N 92 50 54 W	<b>Y</b> <b>(- • - -)</b>			On Samedan Platform A.	BAND: S, X SIGN: SD-EC-320-A. Private aid.  * 48/00

**Note:** Asterisks (\*) indicate that column(s) in which a correction has been made or new information added.  
Denotes a new entry when preceeding the station number.

## SECTION II

CORRECTIONS TO C. G. LIGHT LIST, VOLUME IV LIGHT LIST, 2000							
(1) No.	(2) Name and Location	(3) Position	(4) Characteristic	(5) Height	(6) Range	(7) Structure	(8) Remarks
968	Shell 190-5 Lighted Buoy Marks subsea installation.						Remove from list.
							* 48/00
22880	LOWER GALVESTON BAY OUTER RANGE FRONT LIGHT	29 20 53 N 94 47 31 W	FI W 2.5s FI G 2.5s	42 45		On piles.	Night: visible all around; higher intensity on range line. Day: visible 2° each side of range line.
	*	*	*	*	*	*	* 48/00
22885	LOWER GALVESTON BAY OUTER RANGE REAR LIGHT 3,300 yards, 156.3° from front light.		Oc W 4s Oc G 4s FI W 4s	132 135 40		On skeleton tower on piles. 5	Visible 2° each side of range line.
			*		*	*	* 48/00
22950	LOWER GALVESTON BAY INNER RANGE FRONT LIGHT	29 30 30 N 94 52 22 W	FI W 2.5s FI G 2.5s	42 45		On piles.	Night: visible all around; higher intensity on range line. Day: visible 2° each side of range line.
		*	*	*		*	48/00
22955	LOWER GALVESTON BAY INNER RANGE REAR LIGHT 1,564.3 yards, 336.3° from front light.		Iso W 6s Iso G 6s FI W 4s	116 119 40		On skeleton tower on piles. 5	Visible 2° each side of range line.
			*	*	*	*	* 48/00
35090	- RANGE A FRONT LIGHT	29 10 28 N 95 06 41 W	Q W	17		KRW-I on pile.	For eastbound traffic. Visible all around; higher intensity on rangeline.
		*					48/00
CORRECTIONS TO C. G. LIGHT LIST, VOLUME VI LIGHT LIST, 2000							
(1) No.	(2) Name and Location	(3) Position	(4) Characteristic	(5) Height	(6) Range	(7) Structure	(8) Remarks
25 2275	Mission Bay South Jetty Lighted Buoy 2	32 45 24 N 117 15 30 W	FI R 2.5s			Red.	
	*			*	*	*	48/00
APPROACHES TO SAN DIEGO BAY (Chart 18765)							
Mission Bay							
2275 25	- South Jetty Lighted Buoy 2	32 45 24 N 117 15 30 W	FI R 2.5s			Red.	
	*			*	*	*	48/00
SUSUIN BAY (Chart 18656)							
Carquinez Strait							
6211	- SHORE OIL TERMINAL WHARF LIGHTS EAST (2)	38 03 32 N 122 14 28 W	Q W	10			Private aid.
			*				48/00

**Note:** Asterisks (\*) indicate that column(s) in which a correction has been made or new information added.  
Denotes a new entry when preceeding the station number.

## SECTION II

CORRECTIONS TO C. G. LIGHT LIST, VOLUME VI LIGHT LIST, 2000							
(1) No.	(2) Name and Location	(3) Position	(4) Characteristic	(5) Height	(6) Range	(7) Structure	(8) Remarks
6212	- SHORE OIL TERMINAL WHARF LIGHTS WEST (2)	38 03 32 N 122 14 30 W	<b>Q W</b>	10			Private aid.
			*				48/00
8135	- Entrance Bell Buoy 2	40 45 54 N 124 14 48 W			Red.		
		*					48/00
16740	- <i>Reference Research Lighted Buoy</i>	47 46 43 N 122 26 32 W	<b>FI Y 4s</b>		White and orange.		Private aid.
		*					48/00
18475	- <i>Research Lighted Bouy</i>	47 54 23 N 122 20 54 W	<b>FI Y 4s</b>		White and orange.		Private aid.
		*					48/00
19415	BLAKELY ISLAND LIGHT 2	48 31 53 N 122 48 35 W	<b>FI R 6s</b>	12	5 TR on pile.		
	*	*					48/00
26325	KENAI RIVER LIGHT 3	60 33 00 N 151 15 42 W	<b>FI G 2.5s</b>	20	4 SG on tower.		
						*	48/00
26733	ST. HERMAN HARBOR SOUTH ENTRANCE LIGHT 4	57 46 24 N 152 25 06 W	<b>FI R 6s</b>	5	4 TR on spindle.		
							48/00
27000	NORTHEAST ARM LIGHT 1	57 47 06 N 153 27 12 W	<b>FI G 6s</b>	58	5 SG on small house.		Obscured from 139° to 282.5°.
						*	48/00
27403	FALSE PASS DOCK LIGHTS (4)	54 50 54 N 163 24 06 W	<b>FI R 6s</b>	23	4 On pier.		Private aids.
	*			*	*		48/00
28580	KAMALO POINT LIGHT	21 03 00 N 156 50 54 W	<b>FI W 4s</b>	23	5 NB on spindle.		
	*						48/00

CORRECTIONS TO C. G. LIGHT LIST, VOLUME VII LIGHT LIST, 2000							
(1) No.	(2) Name and Location	(3) Position	(4) Characteristic	(5) Height	(6) Range	(7) Structure	(8) Remarks
11900	- LIGHT 24		<b>FI R 4s</b>	18 5	4 TR on pile.		
	*		*	*	*		48/00
11915	- LIGHT 24A		<b>FI R 4s</b>	17 5	4 TR on pile.		
	*			*		*	* 48/00

**Note:** Asterisks (\*) indicate that column(s) in which a correction has been made or new information added.  
Denotes a new entry when preceeding the station number.

## SECTION II

CORRECTIONS TO C. G. LIGHT LIST, VOLUME VII LIGHT LIST, 2000							
(1) No.	(2) Name and Location	(3) Position	(4) Characteristic	(5) Height	(6) Range	(7) Structure	(8) Remarks
12100	- Obstruction Daybeacon	45 24 12 N 84 38 12 W				NW on pile.	
	*					*	48/00
	<b>Detroit Harbor</b>						
21350	- ENTRANCE LIGHT	45 19 54 N 86 56 12 W	<b>FI W 4s</b>	25 <b>8</b>	8	SG on skeleton tower.	HORN: 1 blast ev 10s. Operates by clicking the Mike 5 times within 5 seconds on VHF-FM Ch. 79 to activate, 7 times within 5 seconds to deactivate. Signal automatically deactivates in 45 minutes. Ra ref.
							48/00

**Note:** Asterisks (\*) indicate that column(s) in which a correction has been made or new information added.  
Denotes a new entry when preceeding the station number.